

Flush Mount FDC Inlet

Designed to provide supplemental water to a building's fire protection system. These units feature a body that's typically concealed behind a wall with only the plate, snoots, and plugs exposed. 250 GPM per inlet. U/L Listed and (2-way only). Contact us for current approvals.

- **4" 2-way standard equipment:** Units are equipped with a brass clappered concealed FDC body w/ 2½" F NPT inlets, wall plate, 2½" F NPT x 2½" F swivel NST snoots, and 2½" plugs. *Vertical configurations utilize brass clapperless FDC bodies w/ 3" F NPT inlets and clappered snoots.
- **6" 2-way standard equipment:** Units are equipped with a brass clappered concealed FDC body w/ 3" F NPT inlets, wall plate, 3" F NPT x 2½" F swivel NST snoots, and 2½" plugs. *Vertical configurations utilize brass clapperless FDC bodies w/ 3" F NPT inlets and clappered snoots.
- **3-way, 4-way, and 6-way standard equipment:** Units are equipped with a schedule 40 steel concealed FDC body w/ 3" grooved inlets, wall plate, 3" F NPT x 2½" F swivel NST clappered snoots, and 2½" plugs.



120PBSA

Part #	Type	Size & Configuration	Outlet Type	Outlet Location	A	B	C
120	2-Way	4" x 2½" x 2½"	Female NPT	Back	10¾"	6"	7"
121	2-Way	4" x 2½" x 2½"	Female NPT	Bottom	11"	5¼"	7"
122	2-Way	4" x 2½" x 2½"	Female NPT	Top	11"	5¼"	7"
123	2-Way	4" x 2½" x 2½"	Groove	Back	10¾"	6½"	7"
124	2-Way	4" x 2½" x 2½"	Groove	Bottom	11"	5¼"	7"
125	2-Way	4" x 2½" x 2½"	Groove	Top	11"	5¼"	7"
126	2-Way	6" x 2½" x 2½"	Female NPT	Back	12"	8¼"	7 5/8"
127	2-Way	6" x 2½" x 2½"	Female NPT	Bottom	12"	7½"	7 5/8"
128	2-Way	6" x 2½" x 2½"	Female NPT	Top	12"	7½"	7 5/8"
126G	2-Way	6" x 2½" x 2½"	Groove	Back	12"	8½"	7 5/8"
127G	2-Way	6" x 2½" x 2½"	Groove	Bottom	12"	7½"	7 5/8"
128G	2-Way	6" x 2½" x 2½"	Groove	Top	12"	7½"	7 5/8"
130	3-Way	6" x 2½" x 2½" x 2½"	Groove	End	25¾"	9¼"	7"
131	3-Way	6" x 2½" x 2½" x 2½"	Groove	Back	25¾"	12-5/8"	7"
132	3-Way	6" x 2½" x 2½" x 2½"	Groove	Top / Bottom	23¼"	9¼"	7"
133	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	End	25¾"	9¼"	7"
134	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	Back	25¾"	12-5/8"	7"
135	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	Top / Bottom	23¼"	9¼"	7"
140	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	End	32¾"	9¼"	7"
141	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	Back	32¾"	12-5/8"	7"
142	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	Top / Bottom	30¼"	9¼"	7"
143	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	End	32¾"	9¼"	7"
144	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	Back	32¾"	12-5/8"	7"
145	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	Top / Bottom	30¼"	9¼"	7"
150	4-Way	6" x 2½" x 2½" x 2½" x 2½" (Square)	Groove	Top / Bottom	16¾"	8¼"	7"
151	4-Way	6" x 2½" x 2½" x 2½" x 2½" (Square)	Groove	Back	15¼"	11"	7"
160	6-Way	6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	End	46¾"	9¼"	7"
160-8	6-Way	8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	End	46¾"	12-7/8"	7"
161	6-Way	6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	Back	46¾"	12-5/8"	7"
161-8	6-Way	8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	Back	46¾"	18"	7"
162	6-Way	6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	Top / Bottom	44¼"	9¼"	7"
162-8	6-Way	8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	Top / Bottom	44¼"	12-7/8"	7"

Specify Finish:

- RB Rough Brass
- PB Polished Brass
- PC Polished Chrome

Specify Wall Plate Lettering:

- A Auto Spkr
- SA Standpipe & Auto Spkr
- S Standpipe
- DS Dry Standpipe

Specify Orientation:

- Horizontal (standard)
- V Vertical

