

## Flush Mount Wall Hydrants / Test Headers (Without Valves)

A hydrant provides an auxiliary outlet for fire department use, while a test header provides a means to flow test a fire pump. These flush mounted units feature a body that's typically concealed behind a wall with only the plate, male snoots, and caps exposed. 250 GPM per outlet.

- **4" 2-way Standard Equipment:** Units are equipped with a brass concealed manifold w/ 2½" F NPT outlets, wall plate, 2½" F NPT x 2½" M NST snoots, and 2½" caps.
- **6" 2-way Standard Equipment:** Units are equipped with a brass concealed manifold w/ 3" F NPT outlets, wall plate, 3" F NPT x 2½" M NST snoots, and 2½" caps.
- **3-way, 4-way, and 6-way Standard Equipment:** Units are equipped with a schedule 40 steel manifold w/ 3" grooved outlets, wall plate, 3" F NPT x 2½" M NST snoots, and 2½" caps.



420RBWH

| Part # | Type  | Size & Configuration                   | Inlet Type | Inlet Location | A    | B       | C      |
|--------|-------|--|------------|----------------|------|---------|--------|
| 420    | 2-Way | 4" x 2½" x 2½"                         | Female NPT | Back           | 10¾" | 6"      | 7"     |
| 421    | 2-Way | 4" x 2½" x 2½"                         | Female NPT | Top / Bottom   | 11"  | 5¾"     | 7"     |
| 420G   | 2-Way | 4" x 2½" x 2½"                         | Groove     | Back           | 10¾" | 6½"     | 7"     |
| 421G   | 2-Way | 4" x 2½" x 2½"                         | Groove     | Top / Bottom   | 11"  | 5¾"     | 7"     |
| 422    | 2-Way | 6" x 2½" x 2½"                         | Female NPT | Back           | 12"  | 7½"     | 7 5/8" |
| 423    | 2-Way | 6" x 2½" x 2½"                         | Female NPT | Top / Bottom   | 12"  | 8½"     | 7 5/8" |
| 422G   | 2-Way | 6" x 2½" x 2½"                         | Groove     | Back           | 12"  | 7½"     | 7 5/8" |
| 423G   | 2-Way | 6" x 2½" x 2½"                         | Groove     | Top / Bottom   | 12"  | 7½"     | 7 5/8" |
| 430    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Groove     | End            | 25¾" | 9¾"     | 7"     |
| 431    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Groove     | Back           | 25¾" | 12-5/8" | 7"     |
| 432    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Groove     | Top / Bottom   | 23¼" | 9¾"     | 7"     |
| 433    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Female NPT | End            | 25¾" | 9¾"     | 7"     |
| 434    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Female NPT | Back           | 25¾" | 12-5/8" | 7"     |
| 435    | 3-Way | 6" x 2½" x 2½" x 2½"                   | Female NPT | Top / Bottom   | 23¼" | 9¾"     | 7"     |
| 440    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Groove     | End            | 32¾" | 9¾"     | 7"     |
| 441    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Groove     | Back           | 32¾" | 12-5/8" | 7"     |
| 442    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Groove     | Top / Bottom   | 30¼" | 9¾"     | 7"     |
| 443    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Female NPT | End            | 32¾" | 9¾"     | 7"     |
| 444    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Female NPT | Back           | 32¾" | 12-5/8" | 7"     |
| 445    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½"             | Female NPT | Top / Bottom   | 30¼" | 9¾"     | 7"     |
| 450    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½" (Square)    | Groove     | Back           | 15¼" | 11"     | 7"     |
| 451    | 4-Way | 6" x 2½" x 2½" x 2½" x 2½" (Square)    | Groove     | Top / Bottom   | 16¾" | 8¾"     | 7"     |
| 460    | 6-Way | 6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | End            | 46¾" | 9¾"     | 7"     |
| 460-8  | 6-Way | 8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | End            | 46¾" | 12-7/8" | 7"     |
| 461    | 6-Way | 6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | Back           | 46¾" | 12-5/8" | 7"     |
| 461-8  | 6-Way | 8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | Back           | 46¾" | 18"     | 7"     |
| 462    | 6-Way | 6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | Top / Bottom   | 44¼" | 9¾"     | 7"     |
| 462-8  | 6-Way | 8" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½" | Groove     | Top / Bottom   | 44¼" | 12-7/8" | 7"     |

**Specify Finish:**

- RB Rough Brass
- PB Polished Brass
- PC Polished Chrome

**Specify Wall Plate Lettering:**

- WH Wall Hydrant
- PT Fire Pump Test

**Specify Orientation:**

- Horizontal (standard)
- V Vertical

